

# AVer EVC130

## Full HD Video Conferencing Endpoint



### Thành phần đóng gói

- Main system unit (codec)
- EVC eCam camera
- EVC microphone array
- IR remote control với Pin
- Power supply
- Các dây cáp
- Thẻ bảo hành
- Hướng dẫn sử dụng

### Các chuẩn giao tiếp

- H.323, SIP and SIP TLS standards
- 64Kbps~4Mbps
- RJ45 network LAN (10/100/1000)
- Manual bandwidth settings

### Camera

- Support for single camera\*
- EVC130 eCam Focus:
  - 2-megapixel CMOS sensor
  - 4X digital zoom
  - ±100° pan; ±25° tilt
  - fixed focus pan/tilt camera
  - Field of view (H): 77°
  - Field of view (V): 45°
  - Field of view (Diagonal): 88°
  - Kensington lock

### Các độ phân giải People video

- HD1080p (1920 x 1080)
- HD720p (1280 x 720)
- 480p (848 x 480)
- 4CIF (704 x 576)
- 4SIF (704 X 480)
- 360p (640 X 360)
- W288p (512 x 288)
- CIF (352 x 288)
- SIF (352 X 240)
- All resolutions at 30fps

### Các độ phân giải Content video

- Supported Resolutions:
  - WSXGA (1440 x 900)
  - HD (1360 x 768)
  - SXGA (1280 x 1024)
  - SXGA (1280 x 960)
  - WXGA (1280 x 800)
  - XGA (1024 x 768)
  - SVGA (800 x 600)
  - VGA (640 x 480)

- Output Resolutions:
  - HD720p (1280 x 720) up to 30fps

### Các chuẩn Video

- H.264, H.264 HP, H.264 SVC, H.263+, H.263, H.261 (available with future firmware upgrade)
- H.239 dual video streams
- BFCP content sharing

### Các đầu vào Video

- EVC eCam camera
- VGA

### Các đầu ra Video

- HDMI
- VGA

### Các chuẩn Audio

- G.711, G.722, G.722.1, G.728, G722.1C licensed from Polycom®

### Các tính năng Audio

- Automatic gain control (AGC)
- Advanced noise reduction
- Acoustic echo cancellation (AEC)

### Các đầu vào Audio

- EVC microphone daisy chain up to 4
- Line-in (3.5 mm)

### Các đầu ra Audio

- Digital audio on HDMI cable
- Line-out (3.5 mm)

### Other supported standards

- H.224, H.225, H.245, H.281, H.323 Annex Q, H.460

### Giao diện người dùng

- Single/dual monitor layout styles



- User-friendly OSD (23 supported languages: English, Traditional Chinese, Simplified Chinese, Czech, Danish, Dutch, Finnish, French, German, Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese-Brazil, Romanian, Russian, Spanish, Swedish, Thai, Turkish, Vietnamese)
- Display/edit site name
  - Supports screen re-layout during playback
  - Playback and file conversion via VCPlayer software (.mov/.mp4 format)
- Speed dialing via hot keys (10 sets)
- Camera presets (10 positions)
- Network Time Protocol (NTP)
- ScreenShare support
- VCLink support

**Network**

- 10/100/1000Mbps
- NAT/firewall traversal
- High Efficiency Lost Packet Recovery (HELPeR™)
- API support via Telnet
- Wake-on-LAN (WOL) support
- IPv4 and IPv6 support
- QoS
- Network Test

**Security**

- AES (Advanced Encryption Standard) function (128-bit)
- Password protection for system settings
- Password protection for remote system management

**Web management tool**

- Remote management through the Web
- Live monitoring via the web
- Firmware update via Ethernet/Internet
- Phonebook download/upload/edit
- Restore system settings

**Value-added features**

- Meeting Recording
  - In meeting and offline recording
  - Save directly to USB flash drive

**Nguồn điện**

- AC 100V~240V, 50/60Hz
- Consumption: EIAJ 12V, 4A

**Dữ liệu môi trường**

- Operation temperature: 0 ~40°C
- Operation humidity: 20% ~80%
- Storage temperature: -20 ~60°C
- Storage humidity: 20% ~80%

**Các kích thước**

- Package dimensions: 292 x 344 x 472 mm
- Package weight: 8.1kg
- Main system (codec): 260 x 158.7 x 33 mm
- eCam Focus camera: 137.7 x 122.3 x 130 mm
- EVC microphone array: 131.9 x 118.6 x 25.5 mm

**Phụ kiện tùy chọn**

- Microphone mở rộng
- Camera Bas gắn tường
- Replacement eCam Focus camera

**Bảo hành**

- 3 năm bảo hành tiêu chuẩn\*

\* Để biết thông tin chi tiết về bảo hành, vui lòng liên hệ đại diện AVer.

eCam Focus Camera



Trước



Sau

